SANIGRID® II
Fiberglass Ceiling Grid System

Sanigrid II is an all-fiberglass ceiling grid system that resists moisture in high humidity and chemical environments. It will not rust, pit, dent or peel like metal grid systems and is easy to install.

The Sanigrid II system uses a series of pre-notched main tees and cross members to lock the grid together. The entire system snaps together quickly for faster installation.

Complete the Sanigrid II Ceiling Grid System with **GLASBORD** ceiling panels.

PRODUCT SPEC

Available Sizes
Ceiling Configuration 2′ x 2′ | 2′ x 4′

Fire Ratings
Class A per ASTM E-84

Available GLASBORD Ceiling Panels
Class C per ASTM E-84
- 0.10″ Pebbled Embossed | CGI
- 0.075″ Pebbled Smooth | PSIF

Class A per ASTM E-84
- 0.09″ Pebbled Embossed | FXE (Factory Mutual)
- 0.10″ | 0.12″ Pebbled Embossed | FX
- Kemply Laminated Panels | ACP

APPLICATIONS
Food Processing Plants
Chemical Processing Plants
Refrigerated Warehouses
Commercial Kitchens
Restrooms

Features
Moisture Resistant
Ideal for High Humidity
Resistant to Chemical Environments
Will Not Rust, Pit, Dent or Peel

11